



Product General Specifications

Base Material	Cross-linked polyolefin	VU 3016
Thickness	2mm (.080") Finished thickness	
MVTR	1.4 lbs / 1000 Sq. Ft. per 24hrs	(Moisture barrier spec)
R value	3.1	(Thermal resistance)
Compression	28% @ 10.5 PSI	(Resistance to compression)
Compression Set	30% @ 30 PSI	(Recovery from compression)
Elongation	215 %	(Elasticity)
Tensile Strength	170 PSI	(Breaking force required)
Tear resistance	25.0 lbs/in	(Notched Breaking force)
IIC	67	
STC	67	

See “STC & IIC The Straight Goods” publication in dealer info binders.

Product Standard Packaging Spec’s

Master Rolls	39” x 370 Lin Ft. (1200 sq.ft./roll) 4 rolls per pallet - 4800 sq.ft.	
100’ Rolls	39” x 30.75 Lin Ft. (1200 Sq. Ft. / Box) 4 boxes per pallet - 4800 S.F.	
Weight	120 lbs / Pallet	

Trademark International

20665 93 Ave. Langley, BC. Canada

Distribution Points: Moncton, NB; St.George, ON; Winnipeg, MB; Saskatoon, SK; Surrey, BC

800-526-5107

www.trademarkinternational.com