

Provincial Series

Thick Face, Long length, Wide Plank, Single Strip Engineered Hardwood Flooring

General Specification

Configuration :	9/16" x 7-1/2" x 6 ft – 3 Layer or 9/16" x 6" x 6 ft – 3 Layer or Plywood base
Face Layer:	4.2mm Sawn Hardwood. (Alt. 5.7mm)
Lengths :	70% full length 6 ft. boards.
Core:	3 Layer or Plywood
Glue lines:	Meets E-1 standard emissions
Moisture:	7%
Finish:	WOCA Oil, or OSMO Hardwax Oil - to order
Colors:	Standard range or Custom colors.
Surface Treatment:	Multiple variations of surface treatment are possible including Antiquing, Brushing, Hand-scraped
T&G Machining: on item)	Standard <u>T&G, Beveled 4 edges or Square edge</u> (depending
Labeled:	Per specification, or Per Sample
Warranty:	Lifetime structural.
Maintenance:	See links to Manufacturers web-pages for instruction. * Maintenance services available from trained professionals.
Specie selection:	White Oak
Stain colors:	See web-site for details / colors.
Grade:	Mixed grade Rustic includes, color & grain variation, sapwood and heartwood mixed, wild grain, burls, filled knots, filled cracks, mineral streaks, etc.
NOTE – Characteristics vary <u>and should not be specified from small samples</u> . Photos are available on the web at www.trademarkinternational.com	
Installation:	Install by “float-in” technique, staple/cleat, or full spread glue.
Radiant Heat:	This specie is warranted over radiant heated floors. Radiant floor installation guide must be followed.
Maintenance:	See Oiled Floor Maintenance. (Also on the web)
Installation site:	Site conditions must be within Industry guidelines as to RH, Sub-floor Moisture etc. Humidifiers or De-humidifiers recommended for RH control between 30 – 50%