

# *Solid Sound*™

## Product General Specifications

---

<b>Base Material</b>	<b>Cross-linked polyolefin</b>	<b>VU 3016</b>
<b>Thickness</b>	<b>2mm ( .080” ) Finished thickness</b>	
<b>MVTR</b>	<b>1.4 lbs / 1000 Sq. Ft. per 24hrs</b>	<b>(Moisture barrier spec)</b>
<b>R value</b>	<b>3.1</b>	<b>(Thermal resistance)</b>
<b>Compression</b>	<b>25% @ 10.5 PSI</b>	<b>(Resistance to compression)</b>
<b>Compression Set</b>	<b>26% @ 30 PSI</b>	<b>(Recovery from compression )</b>
<b>Elongation</b>	<b>215 %</b>	<b>(Elasticity )</b>
<b>Tensile Strength</b>	<b>180 PSI</b>	<b>(Breaking force required)</b>
<b>Tear resistance</b>	<b>25.0 lbs/in</b>	<b>(Notched Breaking force )</b>
<b>IIC</b>	<b>72</b>	
<b>STC</b>	<b>72</b>	

See “ STC & IIC The straight goods” publication included in dealer info binders, on our website or call our sales team for assistance.

## Product Standard Packaging Specifications

---

<b>Master Packs</b>	<b>39” x 370 Lin Ft. ( 1200 Sq. Ft. ) 4 Per Pallet 4800 S.F.</b>	
<b>100’ Rolls</b>	<b>39” x 30.75 Lin Ft. ( 1200 Sq. Ft. / Box ) 4 Per Pallet 4800 S.F.</b>	
<b>Weight</b>	<b>120 lbs / Pallet</b>	

**Trademark International**  
20665 93 Ave. Langley, BC. Canada  
800-526-5107

[www.trademarkinternational.com](http://www.trademarkinternational.com)