

## Engineered, Single Strip Wood Flooring The Simplest Installation System Ever

---

### General Specifications:

<b>Dimensions:</b>	½ x 5" x RL (16" – 48")
<b>Face Layer:</b>	2mm Face, Stained or Natural wood Veneer
<b>Core:</b>	Multi-layer (Birch Base Panel)
<b>Glue lines:</b>	Meets E-1 emission standards.
<b>Moisture:</b>	6 – 8%
<b>Staining:</b>	High accuracy and consistency standard color range.
<b>Finish:</b>	UV Acrylic, multi (7) layered, including Aluminum Oxide.
<b>Gloss:</b>	35 - 40%
<b>T&amp;G Machining:</b>	<u>Licensed Valinge "2G " Loc system</u>
<b>Warranty:</b>	Lifetime structural. 10 Year finish
<b>Specie selection:</b>	Several common North American species and great color range
<b>Grades:</b>	<b>All</b> products are produced in Select grade
<b>Installation:</b>	Product can be floated or glued (full spread).
<b>Radiant Heat:</b>	Please contact office for warranted species or check the sample labels.
<b>Maintenance:</b>	Same as for all natural wood floors.
<b>Installation site:</b>	Site conditions to be within Wood Flooring Industry guidelines.

### **Benefits:**

1. Huge benefits are achieved in lower installation time and cost.
2. Glue down installation goes much easier than with standard T&G.
3. Increased Trademark inventory, means good access to inventory compared with other Imports.



**Trademark International Marketing Inc.**

20665 93 Ave Langley BC  
Phone 604 513 9996 Fax 604 888 9159

Toll Free 1 800 526 5107

[www.trademarkinternational.com](http://www.trademarkinternational.com)

