

Simplicity Collection

Engineered, Single Strip, Wood Flooring The Simplest Installation System Ever

General Specifications:

Dimensions:	½ x 5” x RL (16” – 48”) - 19.7 ft ² per carton.
Face Layer:	Stained or Natural wood Veneer. 2mm Thickness
Core:	Multi-layer (Birch Base Panel)
Glue lines:	Meets E-1 emission standards.
Moisture:	6 – 8%
Staining:	High accuracy and consistency standard color range.
Finish:	UV Acrylic, multi (7) layered, including Aluminum Oxide.
Gloss:	35 - 40%
T&G Machining:	<u>Licensed Valinge “2 G “ Loc system</u>
Warranty:	Lifetime structural. 10 Year finish
Specie selection:	Several common North American species and great color range
Grades:	All products are produced in Select grade
Installation:	Product can be floated or glued (full spread).
Radiant Heat:	Please contact office for warranted species or check the sample labels.
Maintenance:	Same as for all natural wood floors.
Installation site:	Site conditions to be within Wood Flooring Industry guidelines.

Benefits:

1. Huge benefits are achieved in lower installation time and cost.
2. Glue down installation goes much easier than with standard T&G.
3. Increased Trademark inventory, means good access to inventory compared with other Imports.

Trademark International Marketing Inc.

20665 93 Ave Langley BC
Phone 604 513 9996 Fax 604 888 9159
Toll Free 1 800 526 5107

www.trademarkinternational.com