



Emerald Collection

Thick Face Plank & Wide Plank Single Strip Engineered Hardwood flooring.

Configurations :	1. 7/16" x 3-1/2 (10 x 90mm - 4mm face x Length 45cm – 90cm) 2. 9/16 x 5-3/8 (14 x 135mm - 3mm face x Lengths 60cm – 1.8M)
Face Layer:	Sawn Hardwood
Core:	Wood stave or Birch Plywood (depends on specie)
Glue lines:	Meets E-1 standard emissions
Moisture:	7 – 8%
Finish:	Millennium III Ceramic
T&G Machining:	<u>T&G 4 edges, Micro-beveled 4 edges approx. 5mm.</u>
Packed:	Shrink-wrapped cardboard cartons.
Coverage:	<u>Order by Square footage as package quantities vary by configuration.</u>
Labeled:	Mill Standard including carton quantity, dimensions, grade etc.
Warranty:	25 yr finish wear warranty. Lifetime structural.
Specie selection:	Red Oak, Hard Maple, American Cherry, Walnut, Merbau, Teak, Jatoba, Iroko, Doussie, Sycamore, Pacific Walnut, Keruing, White Oak, Kempas.
	NOTE - SEE price sheet for stocked items.
Stain colors:	Inventoried “Walnut Oak”, and “Arizona” – custom staining available on 5,000ft minimum
Grades:	
<u>“Classic”</u>	-Characterized by colour & grain variation, sapwood and heartwood mixed, wild grain, burls, pin knots, minor mineral streaks, etc.
	NOTE – characteristics vary by specie.
<u>“Select”</u>	-Appearance is consistent with the specie and will contain a limited range of colors occurring in that specie. Occasional live pin knots are allowed along with minor mineral streak. Expect variations depending on specie.
Installation:	7/16" Product can be stapled or glued in. 9/16" May be installed by “float-in style” over dense SSM.
Radiant Heat:	Only certain species are warranted over Radiant floors.
Maintenance:	See standard maintenance sheets.
Installation site:	Site conditions must be within Industry guidelines as to RH, Subfloor Moisture etc. Humidifiers or De-humidifiers recommended for RH control between 30 – 50%