

Provincial Collection

Thick Face, Long length, Wide Plank, Single Strip Engineered Hardwood flooring.

General Specification

Configurations :	9/16" x 5-7/8" (14/3 x 148mm x 1860mm)
Alternate:	9/16 x 7-1/2 x 6 foot (15/4 x 189 x 1860)
Face Layer:	3.2mm Sawn Hardwood. (Alt. 4.2mm)
Lengths :	70% full length 6 ft. boards.
Core:	3 Layer Mill option core
Glue lines:	Meets E-1 standard emissions
Moisture:	6 – 7%
Finish:	Natural Oil (Modified Vegetable Oil)
Surface Treatment:	Multiple variations of surface treatment are possible including Antiqueing, Brushing, Hand-scraping & Buffing.
T&G Machining:	<u>T&G -beveled 4 edges</u> (unless Hand-scraped)
Packed:	Shrink-wrapped cardboard cartons.
Labeled:	Mill Standard including carton quantity, dimensions, grade etc.
Warranty:	Lifetime structural.
Maintenance :	Oil finish requires occasional 'vacuum & mop' treatment using Oil infused soap to clean & protect.
Specie selection:	White Oak.
Stain colors:	- Several colors are available using colored Oils. Others are available using standard stains over which Natural Oil is used to finish.
Grade: "ABCD"	Mixed grade includes, colour & grain variation, sapwood and heartwood mixed, wild grain, burls, filled knots, filled cracks, mineral streaks, etc.
NOTE – characteristics vary <u>and should not be specified from small samples.</u> Photo's are available on the web at www.trademarkinternational.com	
Installation:	May be installed by "float-in" technique, stapled, or Full spread Glued.
Radiant Heat:	<u>This series is warranted over Radiant heated floors however such warranty does not claim the floor will not split, crack, or shrink, or curl slightly at the edges. Since this is expected and may be repaired it is not considered warranted condition for repair or replacement</u>
	Radiant floor installation guide must be followed.
Maintenance:	See "Oiled Floor" maintenance sheets. (Also on the web)
Installation site:	Site conditions must be within Industry guidelines as to RH, Sub-floor Moisture etc. Humidifiers or De-humidifiers recommended for RH control between 30 – 50%

Trademark International Marketing Inc.
#2 19405 94 Ave.
Surrey BC Canada
Phone 604 513 9996 or 800 526 5107